

"Products designed with SECURITY in mind!"

SECURCOMM

BY DC SECURITY PRODUCTS

MULTIFLEX CARD CAGE

16 SLOTTED RACK MODEM ENCLOSURE

"Ultimate Flexibility" is our goal at DC Security Products and through our Securcomm Product Line we continue that aim by presenting the **MULTIFLEX CARD CAGE** models **RK16AC** (AC Powered) and **RK16DC** (DC Powered) Rack Mountable Modem Enclosures. The **MULTIFLEX CARD CAGE** series is the perfect compliment to the **MULTIFLEX** family of modem cards. Together, they make up the **P.L.A.N.** (Proprietary Local Area Network) called **FLEX*NET**. The abilities of the **MULTIFLEX** series of products and the use of the lower cost **MULTIFLEX** modem cards create the backbone of **FLEX*NET**. The **MULTIFLEX CARD CAGE** is loaded with options, all developed to effectively perform in a new and / or existing Telco Leased Line / Dialup or as a Line Driver, designed to power a proprietary Dry Copper Campus **P.L.A.N.** environment. Securcomm's **MULTIFLEX CARD CAGE** is the centerpiece of **FLEX*NET**, the dependable transmission solution for your hub or star-configured security communication needs. **FLEX*NET** is the cost effective and time-tested alternative to LAN-based security networks, as well as offering more protection and greater control of your integrated security communication. Let us show you the power of **FLEX*NET**.

Our Securcomm **MULTIFLEX** modem cards can be matched with the **UNIFLEX MODEMS** Models **DC144** and **DC336**, along with the **OMNIFLEX MODEMS** Models **CL1444** and **CL3364**, all of which are important components in **FLEX*NET**. The **MULTIFLEX CARD CAGE** comes in two versions. The **RK16AC** has a universal input voltage range of 85 - 265VAC and a frequency range 47- 440Hz; this allows the **RK16AC** to be installed in many national and international locations. The **RK16DC** has a universal input voltage range of 18 -36VDC; this allows the **RK16DC** to be installed in many self-contained and independently powered environments. The **MULTIFLEX CARD CAGE** is designed to last with all models equipped with power supplies touting a MTBF (Mean Time Between Failures) of 200,000 Hours.

PRODUCT SPECIFICATIONS

MULTIFLEX MODEM CARD COMPATIBILITY:

◆ **RM336**

V.34+, V.32bis, V.32, V.22bis, V.22A&B,
V.23, V.21, BELL 212A, BELL 103J.

◆ **RM144**

V.32bis, V.32, V.22bis, V.22A&B, V.23,
V.21, BELL 212A, BELL 103J.

ENVIRONMENTAL (All Models);

- Temperature -20C To+70C.
- Humidity 90% non-condensing.

APPROVALS (ALL MODELS):

- All Major Domestic and International Approvals

POWER:

◆ **RK16AC:**

-Auto Adjusts to 85-265VAC.

◆ **RK16DC:**

Auto Adjusts to 18-36VDC

POWER CONSUMSION (ALL MODELS):

- 40 Watts

PHYSICAL:

◆ **RK16AC:**

- Length 6.00 inches.
- Width 19.00 inches.
- Height 3.53 inches.
- Weight 9.00 Pounds.
(Unpopulated)
- Weight 18.00 Pounds
(Populated)

PHYSICAL:

◆ **RK16DC:**

- Length 6.00 inches.
- Width 19.00 inches.
- Height 5.00 inches.
- Weight 9.00 Pounds.
(Unpopulated)
- Weight 18.00 Pounds.
(Populated)



**SKIP THE L.A.N...
& GET THE P.L.A.N. (P_{ROPRIETARY} L_{OCAL} A_{REA} N_{ETWORK})...
GET SECURCOMM FLEX*NET!!!**



ONE LINDSAY CIRCLE
SAN FRANCISCO, CALIFORNIA 94124
Voice (415) 550-0443 Fax (415) 550-1780
www.dcsecurityproducts.com